

SACE Tmax
IEC 60947-2

T1B 160
1P



ΔΙΑΝ L x H x P (mm.)
25.4 x 130 x 70

T1B 160
3P



ΔΙΑΝ L x H x P (mm.)
76 x 130 x 70

ΙΙΣΤΙΝΟΪ 1P T1B 160/160 AF
IC = 16 KA AT 380/415 V

TYPE	AMP.	CODE	BAHT
T1B 160 R 16	11.2...16A	LA	3,900.-
T1B 160 R 20	14...20A	LA	3,900.-
T1B 160 R 25	17...25A	LA	3,900.-
T1B 160 R 32	22...32A	LA	3,900.-
T1B 160 R 40	28...40A	LA	3,900.-
T1B 160 R 50	35...50A	LA	3,900.-
T1B 160 R 63	44...63A	LA	3,900.-
T1B 160 R 80	56...80A	LA	3,900.-
T1B 160 R 100	70...100A	LA	3,900.-
T1B 160 R 125	87.5...125A	LA	4,200.-
T1B 160 R 160	112...160A	LA	4,800.-

ΙΙΣΤΙΝΟΪ 3P T1B 160/160 AF
IC = 16 KA AT 380/415 V

TYPE	AMP.	CODE	BAHT
T1B 160 R 16	11.2...16A	LA151101	4,200.-
T1B 160 R 20	14...20A	LA151102	4,200.-
T1B 160 R 25	17...25A	LA151103	4,200.-
T1B 160 R 32	22...32A	LA151104	4,200.-
T1B 160 R 40	28...40A	LA151105	4,200.-
T1B 160 R 50	35...50A	LA151106	4,200.-
T1B 160 R 63	44...63A	LA151107	4,200.-
T1B 160 R 80	56...80A	LA151108	4,200.-
T1B 160 R 100	70...100A	LA151109	4,200.-
T1B 160 R 125	87.5...125A	LA151110	5,000.-
T1B 160 R 160	112...160A	LA151111	5,000.-

SACE Tmax
IEC 60947-2



T1C 160
T1N 160

ΜΕΓΕΘΡΑ L x H x P (mm.)
76 x 130 x 70

ΙΣΧΥΝΟΣ 3P T1C 160/160 AF
IC = 25 KA AT 380/415 V

TYPE	AMP.	CODE	ΒΑΗΤ
T1C 160 R 25	17...25A	LA151123	5,400.-
T1C 160 R 32	22...32A	LA151124	5,400.-
T1C 160 R 40	28...40A	LA151125	5,400.-
T1C 160 R 50	35...50A	LA151126	5,400.-
T1C 160 R 63	44...63A	LA151127	5,400.-
T1C 160 R 80	56...80A	LA151128	5,400.-
T1C 160 R 100	70...100A	LA151129	5,400.-
T1C 160 R 125	87.5...125A	LA151130	6,400.-
T1C 160 R 160	112...160A	LA151131	6,400.-

ΙΣΧΥΝΟΣ 3P T1N 160/160 AF
IC = 36KA 380/415 V

TYPE	AMP.	CODE	ΒΑΗΤ
T1N 160 R 32	22...32A	LA151144	9,000.-
T1N 160 R 40	28...40A	LA151145	9,000.-
T1N 160 R 50	35...50A	LA151146	9,000.-
T1N 160 R 63	44...63A	LA151147	9,000.-
T1N 160 R 80	56...80A	LA151148	9,000.-
T1N 160 R 100	70...100A	LA151149	9,000.-
T1N 160 R 125	87.5...125A	LA151150	9,400.-
T1N 160 R 160	112...160A	LA151151	9,400.-

SACE Tmax
IEC 60947-2

T3N 250
 T3S 250



ขนาด L x H x P (mm.)
 105 x 150 x 70

T2S 160
 T2H 160



ขนาด L x H x P (mm.)
 90 x 130 x 70

โมดูล 3P T2S 160/160 AF
 IC = 50 KA AT 380/415 V

TYPE	AMP.	CODE	BAHT
T2S 160 R 40	28...40A	LA 151225	11,000.-
T2S 160 R 50	35...50A	LA 151226	11,000.-
T2S 160 R 63	44...63A	LA 151227	11,000.-
T2S 160 R 80	56...80A	LA 151228	11,000.-
T2S 160 R 100	70...100A	LA 151229	11,000.-
T2S 160 R 125	87.5...125A	LA 151229.1	12,500.-
T2S 160 R 160	112...160A	LA 151230	12,500.-

โมดูล 3P T2H 160/160 AF
 IC = 70 KA AT 380/415 V

TYPE	AMP.	CODE	BAHT
T2H 160 R 40	28...40A		12,000.-
T2H 160 R 50	35...50A		12,000.-
T2H 160 R 63	44...63A		12,000.-
T2H 160 R 80	56...80A		12,000.-
T2H 160 R 100	70...100A		12,000.-
T2H 160 R 125	87.5...125A		13,500.-
T2H 160 R 160	112...160A		13,500.-

โมดูล 3P T3N 250/250 AF
 IC = 36 KA AT 380/415 V

TYPE	AMP.	CODE	BAHT
T3N 250 R 200	140...200A	LA 151305	13,000.-
T3N 250 R 250	175...250A	LA 151306	13,000.-

โมดูล 3P T3S 250/250 AF
 IC = 50 KA AT 380/450 V

TYPE	AMP.	CODE	BAHT
T3S 250 R 200	140...200A	LA	15,500.-
T3S 250 R 250	175...250A	LA 151316	15,500.-

SACE Tmax
IEC 60947-2



T4N 250
T4N 320
T4H 250
T4H 320

DUVA L x H x P (mm.)
150 x 205 x 103.5

IUSRINEŖS 3P T4N 250/320 AF
IC = 36 KA AT 380/415 V

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
T4N 250 R 250	100...250A	LA 151406	15,000.-
T4N 320 R 320 PR221DS-LS1	128...320A	LA 151407	22,000.-

ŖUSCU GROUND FAULT PROTECTION

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
T4N 320 R320 P222DS/LSIG	128...320A		45,000.-

IUSRINEŖS 3P T4H 250/320 AF
IC = 70 KA AT 380/450 V

DUVA L x H x P (mm.)
105 x 205 x 103.5

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
T4H 250 R 250	100...250A		16,000.-
T4H 320 PR221DS-LS1	128...320A		24,500.-

ŖUSCU GROUND FAULT PROTECTION

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
T4H 320 320 PR222DS/LSIG	128...320A		46,500.-

SACE Tmax
IEC 60947-2



TSN 400
 TSN 630
 TSH 400
 TSH 630

ขนาด L x H x P (mm.)
 140 x 205 x 103.5

โมดูลี 3P TSN 400/630 AF
IC = 36 KA AT 380/415 V

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
TSN 400 R 400 PR221DS-LS/I	100...400A	LA 151502	23,000.-
TSN 630 R 630 PR221DS-LS/I	252...630A	LA 151503	36,000.-

เพิ่ม GROUND FAULT PROTECTION

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
TSN 400 R 400 PR222DS/LSIG	100...400A		44,000.-
TSN 630 R 630 PR222DS/LSIG	252...630A		57,000.-

โมดูลี 3P TSH 400/630 AF
IC = 70 KA AT 380/415 V

ขนาด L x H x P (mm.)
 140 x 205 x 103.5

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
TSH 400 R 400 PR221DS-LS/I	100...400A	LA 151602	25,500.-
TSH 630 R 630 PR221DS-LS/I	252...630A	LA 151603	39,000.-

เพิ่ม GROUND FAULT PROTECTION

TYPE	THERMAL CURRENT ADJ. AMP.	CODE	BAHT
TSH 400 R 400 PR222DS/LSIG	100...400A		46,500.-
TSH 630 R 630 PR222DS/LSIG	252...630A		60,000.-